

Barra Redonda

Bitolas (d)		Peso Linear
pol.	mm	Kg/m
1/4"	6,35	0,25
5/16"	7,94	0,39
3/8"	9,53	0,56
1/2"	12,70	0,99
9/16"	14,29	1,26
5/8"	15,88	1,56
11/16"	17,46	1,88
3/4"	19,05	2,24
13/16"	20,64	2,63
7/8"	22,23	3,05
15/16"	23,81	3,49
1"	25,40	3,98
1.1/16"	26,99	4,49
1.1/8"	28,58	5,04
1.3/16"	30,16	5,60
1.1/4"	31,75	6,221
1.5/16"	33,34	6,85
1.3/8"	34,93	7,52
1.7/16"	36,51	8,22
1.1/2"	38,10	8,95
1.9/16"	39,69	9,71
1.5/8"	41,28	10,50
1.11/16"	42,86	11,32
1.3/4"	44,45	12,18
1.13/16"	46,40	13,06
1.7/8"	47,63	13,98
2"	50,80	15,91
2.1/16"	52,39	16,92
2.1/8"	53,98	17,96
2.1/4"	57,15	20,14
2.5/16"	58,74	21,27
2.3/8"	60,33	22,43
2.7/16"	61,91	23,63
2.1/2"	63,50	24,86
2.9/16"	65,08	26,11
2.5/8"	66,68	27,40
2.3/4"	69,85	30,08
2.13/16"	71,44	31,45
2.7/8"	73,03	32,87
3"	76,20	35,79
3.1/8"	79,38	38,84
3.1/4"	82,55	42,01
3.1/2"	88,90	48,73
3.3/4"	95,35	55,94
4"	101,60	63,64
4.1/16"	103,19	65,65



- Barras de 6m.
- Normalmente fornecida de acordo com a Norma ASTM A 36 J 403/ NBR 7007 MR2. Sob consulta, também poderá ser fornecida de acordo com as Normas ASTM A 572, ASTM A 588 (resistente a corrosão atmosférica), SAE 1020 ou SAE 1045.